SAFETY DATA SHEET

11485-B Gray Multipurpose Matting

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29 CFR 1910,120

Distributor: Absorbents Midwest, Inc. 23040 Industrial Drive, East St. Clair Shores, MI 48080

1-800-877-3116 1-800-877-3096 FAX

Prepared: JANUARY 1, 2019

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: Universal Sorbent Gray Multipurpose

CHEMICAL FAMILY: Olefin, Melamine Resin Solution, Lubricant Blend, Acrylonitrile Polymer Emulsion, Polypropylene

PRODUCT USE: Sorbent Media

CHEMICAL NAME: Polypropylene, Surfactant, Indusco Binder ANB, Indusco MFR, Indolube PPL, Carbon Black Dispersion

WORK PLACE HAZARDOUS MATERIAL INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not a Controlled Product Under WHMIS. WORK PLACE HAZARD: Not applicable.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

TDG CLASSIFICATION: Not Dangerous Goods. PACKAGE GROUP: Not Applicable. PRODUCT IDENTIFICATION NUMBER (PIN): Not Applicable.

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENTS	PERCENT	CAS NUMBER	OSHA PEL	ACGIH TL
Polypropylene	100%	9003-07-0		
	Not A Hazardous Material Under WHMIS			

SECTION III: TOXICOLOGICAL PROPERTIES

HEALTH HAZARDS (acute or chronic): None SIGNS & SYMPTOMS OF EXPOSURE: None MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None

SECTION IV: FIRST AID MEASURES

No special procedures required.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: SPECIFIC GRAVITY: BOILING POINT (C): MELTING POINT (C): SOLUBILITY IN WATER: PERCENT VOLATILE BY VOLUME: Not Applicable **EVAPORATION RATE:** VAPOR PRESSURE (mm Hg): **VAPOR DENSITY** (Air = 1):

Gray Camouflage & 0.88 - 0.92Not Applicable >160 C Insoluble Not Applicable Not Applicable Not Applicable

virtually odor free

JV

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:>329 C (625 F) (setchkin test)FLAMMABLE LIMITS:Not Yet DeterminedEXTINGUISHING MEDIA:Water, Foam, CO2, Dry ChemicalSPECIAL FIRE FIGHTING PROCEDURES:Standard procedures for Class A firesUNUSUAL FIRE AND EXPLOSION HAZARDS:Some carbon monoxide formation is possible under oxygen-leanconditions.Matting will not support combustion.

SECTION VII: REACTIVITY DATA

STABILITY: Stable (XX)
INCOMPATIBILITY (CONDITIONS TO AVOID): None
INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with hot or concentrated nitric and perchloric acid, sulfuric acid or 98% sulfuric acid at 60 C or above.
HAZARDOUS POLYMERIZATION: Will Not Occur (XX)

SECTION VIII: PREVENTIVE MEASURES/SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:None RequiredVENTILATION:None RequiredPROTECTIVE GLOVES:None RequiredEYE PROTECTION:None RequiredOTHER PROTECTIVE EQUIPMENT (SPECIFY):None Required

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in dry area. Do not store near open flame, high heat or strong oxidants. Polypropylene, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire.

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED

No special steps to be taken if material is spilled or released.

WASTE DISPOSAL METHOD

Sanitary landfill or incineration site. Disposal must be done in accordance with local, state and federal regulations.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.