

SAFETY DATA SHEET

18151

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29 CFR 1910.120

SECTION I - IDENTIFICATION

Distributor:

Absorbents Midwest, Inc.
23040 Industrial Drive, East
St. Clair Shores, MI 48080

1-800-877-3116
1-800-877-3096 FAX
Prepared: JANUARY 1, 2019

SECTION II – Hazardous Ingredients/Identity Information

Non-Hazardous

Consists of: Cellulose Fibers >99.5% TLV Units: None established

SECTION III - Physical/Chemical Characteristics

Boiling Point	N/AP	Specific Gravity	N/AP	pH	6-5
Vapor Pressure	N/AP	Melting Point	N/AP		
Vapor Density	N/AP	Evaporation Rate	N/AP		
Solubility in Water:	N/AP	Bulk Density:	13-20 LBS/CU Ft. (Approx)		

Dry Green granule with no odor.

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 1600°F (Open Cup)

Flammable Limits: N/AP LEL: N/AP UEL: N/AP

Extinguishing Media: Standard ABC Fire Extinguisher.

Special Fire Fighting Procedures: Use standard fire protection procedures.

Unusual Fire and Explosion Hazards: May enhance flammability of petroleum based products in open flame.

SECTION V – Reactivity Data

Stable: Yes Hazardous polymerization: Will not occur Conditions to Avoid: Open Flame

Some heat may occur when the product is used to pick up solutions containing concentrated acids.

SECTION VI – Health Hazard Data

Health Hazard: 0 Flammability: 1 Reactivity: 0 (Ranking: Least: 0 Slight: 1 Extreme: 4)

OSHA Health Hazard Classification: NONE. None of the components are listed by IARC, NTP, OSHA or ACGIH as a carcinogen. Symptoms of overexposure acute: At high concentration, irritation of eyes, skin and mucous membranes may occur. Dust Levels: PEL 15MG/M Total, 5MG/M respirable, TLV 10 MG/M – Total, 5 MG/M respirable.

SECTION VII – Precautions for Safe Handling and Use

Waste Disposal Method: Dispose of product in accordance with local, county, state and Federal regulations.

Precautions to be taken in Handling and Storing: If material is released, reclaim material for use. Keep containers dry at all times.

Other precautions: Do not expose to open flame when impregnated with combustible liquids. Treat with same precautions as you would the liquid.

SECTION VIII – Control Measures

Respiratory protection: An OSHA approved dust respirator should be worn when applicable dust standards are exceeded. Eye Protection: Suitable eye protection to safeguard against potential eye contact, irritation, or injury, is recommended. Other equipment: Washing facilities should be available.

Disclaimer: The information contained here is believed to be accurate. However, it is provided solely for the customer's consideration, investigation, and verification. Most of the information originates from suppliers of Absorbents Midwest, Inc., and Absorbents Midwest, Inc., specifically disclaims any and all warranties expressed or implied regarding the accuracy and completeness of such information.